

ERROR StatusLogger Unable to create custom ContextSelector. Falling back to default.

java.lang.ClassCastException: Cannot cast org.apache.logging.log4j.core.async.AsyncLoggerContextSelector to com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ContextSelector

```
    at java.lang.Class.cast(Class.java:3397)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.util.LoaderUtil.newCheckedInstanceOf(LoaderUtil.java:206)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.util.LoaderUtil.newCheckedInstanceOfProperty(LoaderUtil.java:230)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.util.Loader.newCheckedInstanceOfProperty(Loader.java:338)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.createContextSelector(Log4jContextFactory.java:100)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.<init>(Log4jContextFactory.java:61)
    at sun.reflect.NativeConstructorAccessorImpl.newInstance0(Native Method)
    at sun.reflect.NativeConstructorAccessorImpl.newInstance(NativeConstructorAccessorImpl.java:62)
    at sun.reflect.DelegatingConstructorAccessorImpl.newInstance(DelegatingConstructorAccessorImpl.java:45)
    at java.lang.reflect.Constructor.newInstance(Constructor.java:423)
    at java.lang.Class.newInstance(Class.java:442)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.<clinit>(LogManager.java:95)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:55)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
```

```
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for bundle
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ResourceBundleLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for ctx

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ContextMapLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)  
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)  
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for date

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.DateLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

```
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
```

ERROR StatusLogger Unable to create Lookup for env

```
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EnvironmentLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
```

```
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapte
r.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter
.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for event
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EventLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfigurati
on.java:135)
```



```
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
```

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)  
ERROR StatusLogger Unable to create Lookup for java  
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.JavaLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for log4j

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.Log4jLookup

```
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)  
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)  
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for lower

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.LowerLookup

at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for main

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MainMapLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

```
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapte
r.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter
.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for map
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MapLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfigurati
on.java:135)
```



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)  
ERROR StatusLogger Unable to create Lookup for marker  
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MarkerLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for sd

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.StructuredDataLookup

```
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)  
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)  
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for sys

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.SystemPropertiesLookup  
at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

```
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
```

ERROR StatusLogger Unable to create Lookup for upper

```
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.UpperLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.NullConfiguration.<init>(NullConfiguration.java:32)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<clinit>(LoggerContext.java:74)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
```

```
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapte
r.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter
.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for bundle
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ResourceBundleLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfigurati
on.java:135)
```



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)  
ERROR StatusLogger Unable to create Lookup for ctx  
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ContextMapLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for date

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.DateLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)  
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)  
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for env

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EnvironmentLookup  
at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for event

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EventLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

```
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapte
r.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter
.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for java
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.JavaLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfigurati
on.java:135)
```



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)  
ERROR StatusLogger Unable to create Lookup for log4j  
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.Log4jLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for lower

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.LowerLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)  
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)  
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for main

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MainMapLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for map

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MapLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

```
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapte
r.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter
.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for marker
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MarkerLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfigurati
on.java:135)
```



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)  
ERROR StatusLogger Unable to create Lookup for sd  
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.StructuredDataLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for sys

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.SystemPropertiesLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)  
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)  
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for upper

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.UpperLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.<init>(LoggerContext.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.createContext(ClassLoaderContextSelector.java:254)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.locateContext(ClassLoaderContextSelector.java:218)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:123)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.selector.ClassLoaderContextSelector.getContext(ClassLoaderContextSelector.java:117)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:150)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unrecognized format specifier [d]

ERROR StatusLogger Unrecognized conversion specifier [d] starting at position 16 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [thread]

ERROR StatusLogger Unrecognized conversion specifier [thread] starting at position 25 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [level]

ERROR StatusLogger Unrecognized conversion specifier [level] starting at position 35 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [logger]

ERROR StatusLogger Unrecognized conversion specifier [logger] starting at position 47 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [msg]

ERROR StatusLogger Unrecognized conversion specifier [msg] starting at position 54 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [n]

ERROR StatusLogger Unrecognized conversion specifier [n] starting at position 56 in conversion pattern.

ERROR StatusLogger Unable to create Lookup for bundle

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ResourceBundleLookup

at java.lang.Class.asSubclass(Class.java:3432)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)



at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for ctx

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ContextMapLookup

at java.lang.Class.asSubclass(Class.java:3432)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

```
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter
.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for date
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.DateLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory
.java:138)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

```
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for env
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EnvironmentLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory
.java:138)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFacto
ry.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFacto
ry.java:155)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for event

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EventLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for java

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.JavaLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for log4j

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.Log4jLookup

at java.lang.Class.asSubclass(Class.java:3432)



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

```
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for lower
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.LowerLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory
.java:138)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFacto
ry.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
```

```
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
```

ERROR StatusLogger Unable to create Lookup for main

```
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MainMapLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory
.java:138)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFacto
ry.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFacto
ry.java:155)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFacto
ry.java:47)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapte
r.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapte
r.java:47)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)  
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)  
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)  
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for map

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MapLookup

at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for marker

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MarkerLookup

at java.lang.Class.asSubclass(Class.java:3432)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at

com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

```
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter
.java:47)
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for sd
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.StructuredDataLookup
at java.lang.Class.asSubclass(Class.java:3432)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory
.java:138)
```



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

```
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for sys
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.SystemPropertiesLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory
.java:138)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.<init>(Configuratio
nFactory.java:359)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFacto
ry.java:136)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFacto
ry.java:155)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for upper

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.UpperLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:98)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<init>(ConfigurationFactory.java:138)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.<init>(ConfigurationFactory.java:359)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.<clinit>(ConfigurationFactory.java:136)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for bundle

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ResourceBundleLookup  
at java.lang.Class.asSubclass(Class.java:3432)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)  
at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for ctx

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.ContextMapLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

```
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for date
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.DateLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.getConfiguration(ConfigurationFactory.java:470)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
```



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for env

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EnvironmentLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

```
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for event
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.EventLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.getConfiguration(ConfigurationFactory.java:470)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
```

```
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)
    at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
        at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
        at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
        at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
        at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
        at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
        at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
        at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
        at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
        at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
    at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for java
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.JavaLookup
    at java.lang.Class.asSubclass(Class.java:3432)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

```
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for log4j
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.Log4jLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.getConfiguration(ConfigurationFactory.java:470)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
```

```
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for lower
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.LowerLookup
    at java.lang.Class.asSubclass(Class.java:3432)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)



```
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for main
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MainMapLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.getConfiguration(ConfigurationFactory.java:470)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for map

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MapLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

```
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for marker
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.MarkerLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.getConfiguration(ConfigurationFactory.java:470)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
```

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)

at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)

at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)

at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)

at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)

at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)

at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)

at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)

at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)

at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)

at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)

at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unable to create Lookup for sd

java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.StructuredDataLookup

at java.lang.Class.asSubclass(Class.java:3432)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

```
at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for sys
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.SystemPropertiesLookup
    at java.lang.Class.asSubclass(Class.java:3432)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory$Factory.getConfiguration(ConfigurationFactory.java:470)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)
    at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)
```

```
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)
    at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)
at
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)
at
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)
    at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)
    at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)
    at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)
    at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)
    at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)
    at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)
    at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)
at
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultSetStatus(RDBMSResultSet.java:2141)
    at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)
    at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda$1(IntellicusThreadExecutor.java:189)
    at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:624)
    at java.lang.Thread.run(Thread.java:750)
ERROR StatusLogger Unable to create Lookup for upper
java.lang.ClassCastException: class org.apache.logging.log4j.core.lookup.UpperLookup
    at java.lang.Class.asSubclass(Class.java:3432)
```



at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:84)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.lookup.Interpolator.<init>(Interpolator.java:105)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.AbstractConfiguration.<init>(AbstractConfiguration.java:135)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.DefaultConfiguration.<init>(DefaultConfiguration.java:46)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory\$Factory.getConfiguration(ConfigurationFactory.java:470)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.config.ConfigurationFactory.getConfiguration(ConfigurationFactory.java:318)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:690)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.reconfigure(LoggerContext.java:711)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.LoggerContext.start(LoggerContext.java:253)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:155)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.core.impl.Log4jContextFactory.getContext(Log4jContextFactory.java:47)

at com.databricks.client.jdbc42.internal.apache.logging.log4j.LogManager.getContext(LogManager.java:196)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getContext(AbstractLoggerAdapter.java:137)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getContext(Log4jLoggerFactory.java:61)

at  
com.databricks.client.jdbc42.internal.apache.logging.log4j.spi.AbstractLoggerAdapter.getLogger(AbstractLoggerAdapter.java:47)

at  
com.databricks.client.jdbc42.internal.apache.logging.slf4j.Log4jLoggerFactory.getLogger(Log4jLoggerFactory.java:33)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:358)

at com.databricks.client.jdbc42.internal.slf4j.LoggerFactory.getLogger(LoggerFactory.java:383)

at com.databricks.client.jdbc42.internal.apache.arrow.memory.BaseAllocator.<clinit>(BaseAllocator.java:46)

at com.databricks.client.spark.arrow.ArrowBuffer.<init>(Unknown Source)  
at com.databricks.client.spark.jdbc.SparkJDBC42Driver.createArrowBuffer(Unknown Source)  
at com.databricks.client.hivecommon.api.HS2Client.makeRowsetBuffer(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.BackgroundFetcher.<init>(Unknown Source)  
at com.databricks.client.hivecommon.dataengine.HiveJDBCResultSet.moveToNextRow(Unknown Source)  
at com.databricks.client.jdbc.common.BaseForwardResultSet.next(Unknown Source)  
at  
com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.checkResultsetStatus(RDBMSResultSet.java:2141)  
at com.impetus.interaj.dataprovider.rdbms.RDBMSResultSet.run(RDBMSResultSet.java:2159)  
at com.impetus.interaj.utils.IntellicusThreadExecutor.lambda\$1(IntellicusThreadExecutor.java:189)  
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1149)  
at java.util.concurrent.ThreadPoolExecutor\$Worker.run(ThreadPoolExecutor.java:624)  
at java.lang.Thread.run(Thread.java:750)

ERROR StatusLogger Unrecognized format specifier [d]

ERROR StatusLogger Unrecognized conversion specifier [d] starting at position 16 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [thread]

ERROR StatusLogger Unrecognized conversion specifier [thread] starting at position 25 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [level]

ERROR StatusLogger Unrecognized conversion specifier [level] starting at position 35 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [logger]

ERROR StatusLogger Unrecognized conversion specifier [logger] starting at position 47 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [msg]

ERROR StatusLogger Unrecognized conversion specifier [msg] starting at position 54 in conversion pattern.

ERROR StatusLogger Unrecognized format specifier [n]

ERROR StatusLogger Unrecognized conversion specifier [n] starting at position 56 in conversion pattern.